



Product data sheet

ATS4511

16-256 Zone Integrated Security Panel Belgium



ATS4511

16-256 Zone Integrated Security Panel Belgium

Technical specifications

System

Product type	Integrated Access Control
Panel type	Hybrid
No. of keypads / readers	16
Data Gathering Panels (DGP)	15
No. of alarm groups	138
Specified cable	WCAT52 WCAT54

Inputs

Max no. of inputs	256
Onboard inputs	16
ATS1202 support	2

Outputs

No. of outputs	255
No. of onboard outputs	4

Area

No. of areas	16
--------------	----

User/Cards

Max. no. of users	50
Users with name	50
Max. no. of cards	64000
10-digit PIN codes	2000

Access control

Standard doors on control panel	16
Door groups	128
Floor groups	64
Intelligent doors on 4-door DGPs	48

Communication

Onboard transmission type	PSTN
Transmission extension	GSM/GPRS/IP
Databus type	RS485

Event log

Alarm event log	1000
Access event log	1000

Electrical

Power supply type	230 VAC
Power supply value	230 V 50 Hz/23 VAC 56 VA

Physical

Physical dimensions	315 × 445 × 85 mm
Net weight	9700 g
Housing	Large Metal

Environmental

Operating temperature	0 to +50°C
Relative humidity	95% (non-condensing)
Environmental Class	Class II, indoor
IP rating	30

Standards & regulation

EN50131 Grade	Grade 2
Compliance	CE

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 24 January 2019 - 20:19

