

# ATS7200E

## AUDIO REPORTING MODULE (NO ACK)

### Communication devices

---

The advisor MASTER features a true communication centre offering multiple connections (4 Central Stations, each with 2 phone number) and various reporting protocols to report alarms and specified events. All advisor MASTER control panels have a PSTN communicator on board with optional ISDN, GSM, IP communication modules. It is scalable with back-up reporting options according your needs.

The advisor Advanced features a true communication centre offering multiple connections (16 Central Stations) and various reporting protocols to report alarms and specified events. All advisor Advanced control panels have a PSTN communicator on board (or IP and PSTN) with optional ISDN or GSM communication modules. It is scalable with back-up reporting options according your needs.

### Product Overview

---

The Advisor MASTER is capable of playing back recorded voice messages using the optional ATS7200E module. Two modules can be connected per control panel, each having a recording time of 35 seconds divided into 8 messages. Voice messages are programmed to report on the occurrence of specific reporting codes. Some reporting codes are general alarms (Burglar Alarm, Fire Alarm, Tamper Alarm ...), while others are zone specific, that is, you can link a reporting code to specific zones. This means any zone activation or event happening (including technical alarms) can trigger a voice message.

### Voice Reporting

---

A maximum of 2 voice reporting modules can be installed. There are 8 messages per module; the leader or opening message, the address or closing message and 6 alarm messages. If a second module is installed, all 8 messages for the second module will be alarm messages. The ATS7200E first reports the leader message (1) followed by the first alarm messages (3 to 8) and finally the address message (2). These are repeated up to 10 times and then the dialler disconnects and dials again until the maximum number of calls is reached. When a second ATS7200E is installed, all 8 messages of the second unit are alarm messages. Therefore messages 3 to 16 will be available for alarm messages.

### Details

---

- Opening message
- Closing message
- Up to 6 alarm messages
- No Acknowledgement
- Non-volatile memory - Yes, temporary (min. 5 hours)

# ATS7200E

## AUDIO REPORTING MODULE (NO ACK)

### Technical specifications

---

#### General

|              |                              |
|--------------|------------------------------|
| Product line | Advisor Advanced, ATS Master |
|--------------|------------------------------|

#### Network

|                   |               |
|-------------------|---------------|
| Communicator type | Voice / audio |
|-------------------|---------------|

#### Audio

|                    |                                             |
|--------------------|---------------------------------------------|
| Recording capacity | 8 messages (total recording time ~ 35 sec.) |
|--------------------|---------------------------------------------|

#### Electrical

|                     |                                            |
|---------------------|--------------------------------------------|
| Operating voltage   | 12 VDC                                     |
| Power supply value  | 12 VDC via ribbon cable from control panel |
| Current consumption | 50 mA                                      |

#### Physical

|                     |                 |
|---------------------|-----------------|
| Physical dimensions | 80 x 50 x 20 mm |
| Net weight          | 123 g           |

#### Environmental

|                       |                |
|-----------------------|----------------|
| Operating temperature | +10°C to +50°C |
|-----------------------|----------------|

