

DM950I-D

950 Series Manual Call Point With Isolator - Red - Aluminium

General

The DM950I-D is an addressable, 950 series manual call point in a die-cast, aluminum, red housing. It is supplied with a built in, dual isolator module. This push-button-actuated call point is designed according to DIN14655 and is VdS approved (G 204003). Activation is indicated with an LED. The door is secured by key and houses the activation window which is replaceable.

Operation and Use

The DM950 series manual call points are designed for use with Aritech addressable fire panels running 900 series protocol. The built-in dual isolator allows the call point to remain operational even in the event of a single short circuit on the cable on either side of the call point.

Accessories

Accessories normally supplied with the call point may also be ordered separately.

- Spare key (DM800KEY)
- Replacement glass (DM864B)



Details

- Manual call point in durable aluminum die-cast metal housing
- Conforms to DIN 14655
- Protocol compatible with 950 series devices
- Door secured by key
- Replaceable window
- Includes alarm LED and dual isolator
- Inscription "Feuerwehr"
- VdS approved

DM950I-D

950 Series Manual Call Point With Isolator - Red - Aluminium

Technical specifications

Physical

Physical dimensions	125 x 125 x 34 mm (W x H x D)
Net weight	400 g
Colour	Red (RAL 3000)

Environmental

Operating temperature	-20 to +70°C
Environment	Indoor
IP rating	IP44

Standards & regulation

Certification	EN54-11
---------------	---------

Power supply

	12 - 28 VDC
--	-------------

Current consumption

Standby	150 µA
Alarm	4 mA

Door opening angle

	>160°
--	-------

Colour

	Red - RAL3000
--	---------------

