

ISM-95

2000/900 Series Isolator Module w/ CPD Housing

General

The ISM-95 is a stand-alone loop isolator that may be used for protection of both 2000 and 900 series addressable loops. It is supplied in a CPD approved enclosure for easy installation.

The ISM-95 senses and isolates overload and short circuit faults on the addressable device loop. A yellow LED on the PCB indicates an isolation condition. Any device connected to the auxiliary device terminals continue to operate in the event of a single short circuit fault on either side.

Functionality and use

The function of the ISM-95 is to protect the integrity of the addressable loop in case of an overload or short-circuit on part of the loop. In such event the entire data circuit is not lost but only the effected part of the loop is isolated.

For full protection it is recommended that every addressable device in the loop be fitted with a ISM-95 isolator. For regulatory purposes it is specified that not more than a single detection zone is affected by a single fault on the loop, containing no more than 32 devices.



Details

- Protection against overload conditions
- Automatic restore when fault is corrected
- Local isolated indication
- Device connected to isolator remains operational
- CPD Approved

ISM-95

2000/900 Series Isolator Module w/ CPD Housing

Technical specifications

Electrical

Operating voltage	17 to 28 VDC
-------------------	--------------

Physical

Physical dimensions	89 x 43 x 37 mm (H X W X D)
---------------------	-----------------------------

Net weight	147 g
------------	-------

Environmental

Operating temperature	-10 to +50°C
-----------------------	--------------

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP55
-----------	------

Standards & regulation

Certification	EN54-17
---------------	---------

Current consumption

Standby	0.7 mA
---------	--------

Isolated	< 1.6 mA
----------	----------

Passing current (max)	800 mA
-----------------------	--------

Line resistance

Normal	0.1 Ohms
--------	----------

Switching voltage

Normal to isolated	14 V
--------------------	------

Isolated to normal	14.5 V
--------------------	--------

Isolation line

Negative breaking isolator

